

# PH-200: Waterproof pH Meter

Ideal for all pH testing, water purification applications, wastewater regulation, aquaculture, hydroponics, colloidal silver, labs & scientific testing, pools & spas, ecology testing, boilers & cooling towers, water treatment, wine, coffee, agriculture and more.

## Features:

- Measures pH and Temperature
- Auto-ranging three point calibration with digital fine tuning
- Includes 4 pH buffer solution in a sponge embedded in a clear cap
- Waterproof housing (IP-67 rating)
- Simultaneous temperature display
- Measurement Range: 0-14 pH
- Digital automatic calibration (one point), with digital fine tuning
- Auto-off function, data-hold function and low-battery indicator
- Display: large and easy-to-read LCD screen includes simultaneous temperature reading
- **Factory Calibrated:** The PH-200 meter is three-point factory calibrated to 4, 7, and 10 pH. The meter can be recalibrated with digital calibration using the push buttons, rather than a screwdriver.
- Includes a cap, batteries, lanyard, and pH 7.0 buffer
- Warranty: 1 Year

## Specifications

Item Number: 66761

pH Range: 0 - 14

Temperature Range: 0-80 °C; 32-176 °F

Resolution: 0.01 pH; Temperature resolution is 0.1 °C/F

Accuracy: +/- 0.02 pH

Calibration: Digital automatic calibration (one point) with digital fine tuning

Electrode: Replaceable glass sensor and reference tube electrodes

Housing: IP-67 Waterproof (submersible; floats)

Power source: 3 x 1.5V button cell batteries (included)

Dimensions: 18.5 x 3.4 x 3.4 cm (7.3 x 1.3 x 1.3 inches)

Weight: 96.4 g (3.4 oz)



Manufactured by:  
HM Digital, Inc.,  
Culver City, CA

WaterGroup  Companies Inc.

[www.hydrotechwater.com](http://www.hydrotechwater.com) | [www.watergroup.com](http://www.watergroup.com) | [www.petwa.ca](http://www.petwa.ca)



#57801 1/10

\* When ordering Petwa products, the appropriate prefix will be applied.