AQUA FLO®

CGAC SERIES

Granular Activated Carbon Cartridges

Aqua Flo CGAC Series Cartridges effectively reduce unwanted tastes and odors, including chlorine taste & odor from your drinking water. They are designed to allow maximum contact between the water and carbon, ensuring optimal adsorption, providing good general-purpose drinking water filtration.

FEATURES / BENEFITS:

- Effective reduction of bad taste & odor and chlorine & odor reduction
- Designed for optimal adsorption
- Post-filter to reduce carbon fines
- Available in Four Sizes: 2.5x10"; 2.5x20"; 4.5x10"; 4.5x20"
- Universal fit Fits most standard water filter housing
- Micron not rated

SPECIFICATIONS:

- End Caps Polypropylene
- Gasket SBC Rubber
- Filter Media Granular Activated Carbon
- Outer Casing Polypropylene
- Post Filter Polypropylene
- ◆ Temperature Rating 40 125°F (4 -52°C)

APPLICATIONS (For water filtration only):

- Commercial/Residential Drinking Water Filtration
- Food & Beverage Filtration
- Industrial Water Filtration
- Chlorine reduction for process water



"Effectively reduce unwanted tastes and odors, including chlorine taste & odor from your drinking water."

CGAC SERIES

Granular Activated Carbon Cartridges

SPECIFICATIONS & PERFORMANCE:

ITEM#	DESCRIPTION	DIMENSIONS	CASE QTY	SHIP WEIGHT EACH (LBS)	RATING (NOMINAL)	FLOW RATE (GPM)
26277	CGAC-10	2.5" x 10" (63.5 x 254 mm)	20	1.0	NR	1.0 US GPM (3.8 LPM)
26186	CGAC-20	2.5" x 20" (63.5 x 508 mm)	12	2.0	NR	2.0 US GPM (7.5 LPM)
26187	CGAC-10BV	4.5" x 10" (114.3 x 254 mm)	12	1.9	NR	2.0 US GPM (7.5 LPM)
26188	CGAC-20BV	4.5" x 20" (114.3 x 508 mm)	6	3.8	NR	4.0 US GPM (15.1 LPM)

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

NOTE: Initial flow pressure drop less than 5 psi at rated flow rate. Change filter when pressure drop exceeds 10 psi.



Your Local Water Specialist