Hydrotech

89 Control Valve





Features:

- True 1" porting for high flow rates. Up to 18" softeners and 18" filters
- High-efficiency Performance. Up Flow Regeneration with Optimal Precision Brining or Down Flow Regeneration.
- Adjustable backwash frequency saves up to 2,000 gallons of water per year
- Large 4 line Touch Pad LCD display customizable for dealership
- Automatic Reserve adjusts based on actual usage
- Automatic System Flush refreshes system during periods of non use preventing bacteria growth
- Soft Water Recharge performs quick regeneration ensuring you never run out of soft water
- Soft Water Brine Tank Refill conserves capacity and keeps brine tank clean
- Time saving quick connect features on bypass, drain line and powercord
- Up Flow meter delayed; Down Flow Softener meter delayed, days of week, calendar clock, meter immediate, meter override
- Self charging capacitor keeps date / time of day for 48 hours while programming remains in permanent memory
- integrated turbine meter
- Comes with 1" elbow NPT
- Five Year Control Valve Warranty

Specifications		
Valve Body Material	Noryl (PPO)	
Plumbing Connections (NPT	Straight 1"	
Tank Thread	2-1/2" NPSM	
Adjustable Cycles	0 - 99 minutes	
Regeneration	Up Flow /Down Flow	
Meter Accuracy	+/-5%	
Maximum Meter Capacity	99,999 GAL	
Distributor Pilot	1.05"	
Drain Line	3/4"	
Brine Line	3/8"	
Flow Rates (Valve Only 50 psi inlet)		
Continuous (15 psi drop)	27 GPM	
Peak (25 psi drop)	35 GPM	
Max. Backwash (25 psi drop)	27 GPM	
Cv	7	
Typical Applications		
Softeners	up to 18" Diameter	
Filters	up to 18" Diameter	
Electrical		
Input	110V AC 50/60Hz	
Output	12V AC 50/60Hz 650mA	
Certification	cUL	
Operation Ratings		
Max. Working Pressure	20 - 125 psi	
Max. Temperature	34F - 100F	
Approvals		
NSF/ANSI 44	Certified	
Additional Information		
Shipping Weight	7 pounds	

Specifications

89 Control Valve

Part #	Description
10010044	89UF ELECTRONIC METER-BLACK COVER
10010043	89DF ELECTRONIC METER-BLACK COVER

CONTROL VALVE INCLUDES BYPASS AND 1" 90° ELBOW NPT CONNECTORS

VALVES CAN EASILY BE CONVERTED FROM SOFTENER TO FILTER

Your Local Water Treatment Professional





Toll Free: 1-877-288-9888 www.hydrotechwater.com

Regina, SK • Cambridge, ON • Whitestown, IN Houston, TX • Phoenix, AZ • Guadalajara, MX