



PPC SERIES

Pleated Polyester Reusable Filter Cartridges

The Aqua Flo PPC cartridge filters are made from reusable polyester fibers which are pleated to maximize dirt holding capacity. These are excellent multi-purpose sediment filters.



FEATURES / BENEFITS:

- ◆ Pleated design maximizes filtration area for lower initial pressure drop
- ◆ Durable, versatile and reusable
- ◆ Polyester media is bacteria and chemical resistant
- ◆ Available in four sizes: 2.5x10"; 2.5x20"; 4.5x10"; 4.5x20"
- ◆ Universal fit – Fits most standard water filter housings
- ◆ Available in four micron ratings: 1; 5; 30; 50

SPECIFICATIONS:

- ◆ Filter Media – Non-Woven Polyester
- ◆ End Caps – Vinyl Plastisol
- ◆ Core – Polypropylene
- ◆ Temperature Rating – 39 - 125°F (4 -52°C)

APPLICATIONS (For water filtration only):

- ◆ Commercial/Residential Drinking Water Filtration
- ◆ RO Pre-filtration
- ◆ Cooling Tower Filtration
- ◆ Chill Water Loop Filtration
- ◆ Food & Beverage Filtration
- ◆ Industrial Water Filtration



**“Excellent
multi-purpose
sediment filters.”**

PPC SERIES

Pleated Polyester Reusable Filter Cartridges

SPECIFICATIONS & PERFORMANCE:

ITEM #	DESCRIPTION	DIMENSIONS	CASE QTY	SHIP WEIGHT EACH (LBS)	RATING (NOMINAL)	FLOW RATE (GPM)
26174	PPC-1-10	2.5" x 10" (63.5 x 254 mm)	50	0.25	1	7 US GPM (26.5 LPM)
26175	PPC-5-10	2.5" x 10" (63.5 x 254 mm)	50	0.25	5	7 US GPM (26.5 LPM)
26162	PPC-30-10	2.5" x 10" (63.5 x 254 mm)	50	0.2	30	7 US GPM (26.5 LPM)
26163	PPC-50-10	2.5" x 10" (63.5 x 254 mm)	50	0.2	50	7 US GPM (26.5 LPM)
26176	PPC-1-20	2.5" x 20" (63.5 x 508 mm)	25	0.7	1	14 US GPM (52.9 LPM)
26177	PPC-5-20	2.5" x 20" (63.5 x 508 mm)	25	0.7	5	14 US GPM (52.9 LPM)
26160	PPC-30-20	2.5" x 20" (63.5 x 508 mm)	25	0.7	30	14 US GPM (52.9 LPM)
26161	PPC-50-20	2.5" x 20" (63.5 x 508 mm)	25	0.7	50	14 US GPM (52.9 LPM)
26165	PPC-1-10BV	4.5" x 10" (114.3 x 254 mm)	20	0.6	1	15 US GPM (56.7 LPM)
26178	PPC-5-10BV	4.5" x 10" (114.3 x 254 mm)	20	0.6	5	15 US GPM (56.7 LPM)
26242	PPC-30-10BV	4.5" x 10" (114.3 x 254 mm)	20	0.5	30	15 US GPM (56.7 LPM)
26243	PPC-50-10BV	4.5" x 10" (114.3 x 254 mm)	20	0.5	50	15 US GPM (56.7 LPM)
26168	PPC-1-20BV	4.5" x 20" (114.3 x 508 mm)	10	0.86	1	30 US GPM (113.4 LPM)
26180	PPC-5-20BV	4.5" x 20" (114.3 x 508 mm)	10	0.86	5	30 US GPM (113.4 LPM)
26244	PPC-30-20BV	4.5" x 20" (114.3 x 508 mm)	10	0.75	30	30 US GPM (113.4 LPM)
26169	PPC-50-20BV	4.5" x 20" (114.3 x 508 mm)	10	0.75	50	30 US GPM (113.4 LPM)

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

NOTE: Initial flow pressure drop less than 5 psi at rated flow rate. Change filter when pressure drop exceeds 10 psi.

Your Local Water Specialist

AQUA FLO®

A Division of

