

Hydrotech[®]

NRV (Non-Regenerating Valve) Whole House Catalytic Carbon Filter

Economical Reduction of Chlorine, Chloramines and Other Bad Taste & Odors

Once water arrives safely at your home there is no further need for disinfectants. In fact they are undesirable! Disinfectants cause taste and bad odor, dry skin, damage plumbing, and can produce potentially harmful by-products.



**97% Chlorine
Removal!
Over 1,100,000
gallons**



Certified by IAPMO R&T
to NSF/ANSI 42 for
Chlorine Reduction



NRVTOC-150



Features:

- Economical whole-house catalytic carbon filtration solution for reducing chloramines, chlorine and other bad tastes and odors. TOK models reduce chlorine plus hydrogen sulfide (H2S) caused by sulphate reducing bacteria common in warmer climates.
- Includes factory installed one-piece bypass
- Time saving quick connect fittings (90° 3/4" NPT Elbows) included for faster, easier installation. Optional quick connect SharkBite® fittings also available.
- Five year warranty on Distribution Head.
- Ten Year Warranty on NSF Certified tank.

90° 3/4" NPT Elbows



Economical non-back-washing distribution head with convenient quick connect fittings

Options:

- Pressure tanks also available in Blue and Natural colours.

Specifications	NRVTOC-100	NRVTOC-150	NRVTOC-200	NRVTOC-250	NRVTOCK-100	NRVTOCK-150
	Black Tank 15550952	Black Tank 15550953	Black Tank 15550954	Black Tank 15550956	Natural Tank 15054093	Natural Tank 15054094
Peak Flow Rates	4.0 gpm	5.0 gpm	7.0 gpm	8.0 gpm	4.0 gpm	5.0 gpm
Filter Media Volume - Cubic Feet	1.0 ft ³	1.5 ft ³	2.0 ft ³	2.5 ft ³	1.0 ft ³	1.5 ft ³
Filter Tank Size (inches)	9 x 48	10 x 54	12 x 52	13 x 54	9 x 48	10 x 54
Media Type	Catalytic Carbon	Catalytic Carbon	Catalytic Carbon	Catalytic Carbon	Catalytic Carbon With KDF Distributor	Catalytic Carbon With KDF Distributor
Media Loaded	Yes	Yes	Yes	No	Yes	Yes
KDF Protector	No	No	No	No	Yes	Yes
Tank Jacket	No	No	No	No	No	No
Shipping Weight	60 lbs	78 lbs	95 lbs	111 lbs	60 lbs	78 lbs
Plumbing Connections	Includes 3/4" 90° Elbows NPT. Bypass Included					
Electrical Requirements	None					
Water Temperature	Min 39 - Max. 100 degrees Fahrenheit					
Water Pressure	Max. 125 psi					

The life expectancy of the carbon media bed in these units will be reduced as compared to a back washing style carbon filter. The actual media bed life will vary depending on water consumption, chlorine/chloramines concentration and flow rate. Exceeding the peak flow rate listed above will drastically reduce the life expectancy of the carbon media.



Certified by IAPMO R&T
to NSF/ANSI 42 for
Chlorine Reduction



Hydrotech®

A Division of



TOLL-FREE: 1-877-288-9888
www.hydrotechwater.com

Regina, SK • Cambridge, ON • Whitestown, IN • Houston, TX • Phoenix, AZ • Guadalajara, MX

Your Local Water Treatment Professional

80153049 2023-10-03
Available in print