

AQUA FLO[®]

PLATINUM

P-LR-1-10

Lead & Chemical Reduction Filter Cartridge



The **Aqua Flo P-LR-1-10 Cartridge** is an ultra-high performance activated carbon filter designed to reduce Lead, Volatile Organic Compounds (VOC), Trihalomethanes (THM), and chlorine from potable water. It is also highly effective in improving water taste and odor.

The cartridge is made from high quality activated carbon constructed in a proprietary compact style to deliver high adsorption performance and excellent contaminant removal characteristics.

P-LR-1-10 cartridge is an ideal choice for a wide range of residential, food service, institutional, and commercial applications.

FEATURES / BENEFITS:

- ◆ Made of premium quality activated carbon with proprietary media
- ◆ Block construction maximizes performance
- ◆ Highly effective (> 95%) in reduction of Lead VOC and chlorine, taste/ odor up to 600 US Gal (2,271 litres)
- ◆ 1µ particulate reduction
- ◆ Universal fit – can be used with most standard 10” filter housings

SPECIFICATIONS:

- ◆ End Caps – Polyethylene
- ◆ Filter Media – Acid Washed Activated Carbon (Coconut Shell Based)
- ◆ Temperature Rating – 39 - 122F (4- 50C)

APPLICATIONS (For water filtration only):

- ◆ Commercial/Residential Drinking Water Filtration
- ◆ Food & Beverage Filtration
- ◆ Industrial Water Filtration
- ◆ Lead & chemical reduction for process water



P-LR has been tested and certified by CSA Group to NSF/ANSI 53 for reduction of Lead, VOC, and to NSF/ANSI 42 for reduction of chlorine, taste and odor.

Certified for use with Aqua Flo model 36999*.

*CSA certification does not extend for use with other housings & systems.

P-LR-1-10

Lead Removal Filter Cartridge

SPECIFICATIONS & PERFORMANCE:

| ITEM# | MODEL | MICRON RATING | LENGTH (INCH) | O.D (INCH) | I.D (INCH) | END TYPE | RATED FLOW | RATED LIFE | MAX. OPERATING TEMP |
|-------|-----------|---------------|---------------|------------|------------|-----------------|-------------|-------------------|---------------------|
| 36209 | P-LR-1-10 | 1μ | 9.75" | 2.65" | 1" | Single Open End | 0.75 US GPM | 600 gal (2,271 L) | 100°F (~38°C) |

NOTE: Micron rating and dimensions are nominal

Your Local Water Specialist

AQUA FLO®

A Division of

